

## RECEIPT PRINTER MOD. UNO



### PRINTER SET

<input checked="" type="checkbox"/> 1 Printer mod. Uno	<input checked="" type="checkbox"/> 1 Multipolar Connection Cable (1.5 mt.)
--	---

### MAIN FEATURES

#### Print-out of:

<input checked="" type="checkbox"/> Trip receipt	<input checked="" type="checkbox"/> Fare Register
<input checked="" type="checkbox"/> Credit-card voucher	<input checked="" type="checkbox"/> Maximum speed
<input checked="" type="checkbox"/> 20 + 20 memory totals	

### HARDWARE

<input checked="" type="checkbox"/> Printer case in ABS/Polycarbonate	<input checked="" type="checkbox"/> Red led status indicator
<input checked="" type="checkbox"/> Printer mechanism Epson M 150 II	<input checked="" type="checkbox"/> ON-OFF switch
<input checked="" type="checkbox"/> Dimensions: H mm, D mm, L mm	

### GENERAL SPECIFICATIONS

<input checked="" type="checkbox"/> Printing method :	Impact Dot matrix
<input checked="" type="checkbox"/> Print speed 1 dot line :	Approx. 100 ms (continuous printing)
<input checked="" type="checkbox"/> 5 x 7 dot matrix :	Approx. 1.5 L/S (continuous printing)
<input checked="" type="checkbox"/> Paper :	Normal paper 44 m/m x 40 m/m diameter
<input checked="" type="checkbox"/> Inking :	Ribbon cassette

### WORKING CONDITIONS

<input checked="" type="checkbox"/> Temperature range (operation) :	0 ° C to + 50 ° C
<input checked="" type="checkbox"/> Temperature range (conservation) :	- 25 ° C to + 70 ° C
<input checked="" type="checkbox"/> Humidity range (operation) :	10% to 95% without condensation
<input checked="" type="checkbox"/> Humidity range (conservation) :	Up to 95% without condensation
<input checked="" type="checkbox"/> Vibration (operation) :	0.5 G - 10, 55, Hz/min X, Y, 1H
<input checked="" type="checkbox"/> Vibration (conservation) :	2.0 G - 10, 55, Hz/min X, Y, 1H
<input checked="" type="checkbox"/> Reliability:	MCBF 5 X 10 5 lines